



KEY TO SYMBOLS


The symbols shown below are used in CC Höganäs product catalogues, data sheets, etc. to indicate the properties of ceramic tiles. Please note that these symbols should be considered as a general guide to how and where a particular type of tile can be used. When choosing tiles, you should consult your supplier for confirmation that they are suitable for the application and environment you have in mind.



Light duty floor. Light pedestrian traffic only, e.g. in home kitchens, hallways, bathrooms and toilets.




Normal floor. Strong enough for pedestrian traffic and light rubber-wheeled trolleys, e.g. in porches, foyers, stairways, showrooms, churches and shops.




Heavy duty floor. Suitable for floors subjected to hard wear and tear from hard-wheeled trolleys, handtrucks, e.g. in kitchens, storehouses, stores.




Industrial duty floor. Suitable for floors subjected to heavy loads and mechanical wear from heavy traffic, trucks, lorries e.g. in factories, warehouses and fire stations.




Floor heating. Tiles suitable for floors with floor heating. Water absorption max. 6%.



Non skid. Safety tile with high-friction surface.



Light duty wall. Suitable for kitchens, hallways, bathrooms, shower stalls, etc. in the home as well as for foyers, showrooms, waiting rooms, shops, etc.



Heavy duty wall. Resistant to wear and tear and easy to keep clean. Recom. for public toilets, public baths, factories, schools, restaurant kitchens, warehouses, laundries, boilerhouses, fire stations etc.



Frostproof. Suitable for verandas, outdoor steps, outer doorways and cold stores. Tiles with this classification have a maximum water absorption of 0.5% by weight.



Frost resistant. Suitable for outdoor use in cold climates on vertical walls or if bedded in sand, but not for bedding in mortar on horizontal surfaces exposed to frost.



Chemical resistant. Immune to attack by most acids, alkalis and solvents.



Stair tread. Tile with overhang at front edge.



Swimming pool. Suitable for use in swimming pools, shower rooms and washrooms.